

## **1U 19" Rackmount LCD Console - USB + PS/2**

*StarTech ID: RKCONS1901EU*



The RKCONS1901EU 1U 19" Rack Mount LCD Console provides a complete keyboard, video and mouse control point, integrated neatly into only 1U of rack/cabinet space - providing complete KVM control right from a server rack.

Offering a durable, compactable 1U design, when the rack console is not in use it's as simple as folding the display like a laptop computer, and sliding it back into the server rack on the sturdy mounting rails (included). The included key lock provides an added security layer, helping to reduce unauthorized access to connected computers.

Offering consolidated control from a convenient location, the KVM rack console can be connected to virtually any multiport KVM switch, for control of multiple servers/computers, providing a scalable KVM control solution that lets you determine the type of KVM switch to use based on function and budget.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

### **Applications**

- Centralized control of dozens of PCs and servers if used with optional KVM
- Improving the internal space efficiency of existing cabinets
- Managing cabinet mounted servers

## Features

- Bright 19" Active Matrix TFT Display
- VGA video input support
- Compatible with USB or PS/2 PCs and KVMs
- Durable 1U rack-mountable design
- OSD function (On Screen Display) for LCD display
- Security features, including port locking and auto scan

**Technical Specifications**

Warranty	2 Years
Audio	No
Display Size	19in
Key Lock	Yes
KVM Ports	1
Multi-Monitor	No
Panel Type	Active Matrix TFT LCD
PC Interface	USB and PS/2
PC Video Type	VGA
Rack-Mountable	Yes
Aspect Ratio	Standard (4:3)
Brightness	250 cd/m <sup>2</sup>
Color Depth	24-bit, 16.7M colors (Truecolor)
Contrast Ratio	1000:1
IP Control	No
Maximum Analog Resolutions	1280x1024(SXGA)@60Hz
Maximum Number of Users	1
MTBF	60,000 Hours
Pixel Pitch Support	0.294 x 0.294 mm
Port Selection Support	Hotkeys and OSD (On Screen Display)
Response Time	5ms
Viewing Angle	176° (H), 170° (V)
Host Connectors	1 - USB A (4 pin) Female
Host Connectors	1 - VGA (15 pin; High Density D-Sub) Female
Host Connectors	2 - PS/2 (6 pin; Mini-DIN) Female
OS Compatibility	OS independent; No software or drivers required
Color	Black
Enclosure Type	Heavy Duty Steel
Maximum Mounting Depth	800 mm [31.5 in]
Minimum Mounting Depth	555 mm [21.9 in]
Product Height	45 mm [1.8 in]
Product Length	575 mm [22.6 in]
Product Weight	13.7 kg [30.3 lb]

Product Width	480 mm [18.9 in]
Input Voltage	100 ~ 240 AC
Operating Temperature	0°C to 50°C (32°F to 122°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Shipping (Package) Weight	19.5 kg [43.1 lb]
Included in Package	1 - 1U LCD Rack Console Drawer
Included in Package	1 - Mounting Rails - Set
Included in Package	1 - Console Cable Kit
Included in Package	1 - Power Cord
Included in Package	1 - Set of Keys
Included in Package	1 - Set of Mounting Screws
Included in Package	1 - User Manual
Included in Package	1 - Manual on CD

### Certifications, Reports and Compatibility

